



## Quality and performance in an affordably priced application tape.

ApliTape™ is the original RTape application tape. It has all of the great features of RTape's popular Conform® series, but without the RLA® Release Liner Adhesive additive. Available in standard and heavyweight paper grades, in a variety of tack levels.

### 4000 Low Tack

Standard grade saturated paper premask, coated with a low tack rubber adhesive.

### 4050 Medium Tack

Standard grade saturated paper application tape, coated with a medium tack rubber adhesive.

### 4075 High Tack

Standard grade saturated paper application tape, coated with a high tack rubber adhesive.

#### Applications

- General Purpose Sign Applications
- Screen Printing
- Digital Printing

#### Product Information


- Factory cut, razor slit rolls
- Rubber adhesive
- Available in a variety of tack levels
- No adhesive build-up on stored graphics
- Works in either wet or dry applications
- No adhesive balls, gapping between layers or crushed edges



## TECHNICAL DATA ▶

Physical Properties		4000	4050	4075
Color		White/Translucent	White/Translucent	White/Translucent
Adhesive		Rubber-Based	Rubber-Based	Rubber-Based
Caliper	Facestock	4.0 - 4.5 mil (100-113 μ)	4.0 - 4.5 mil (100-113 μ)	4.0 - 4.5 mil (100-113 μ)
	Facestock + Adhesive	5.0 - 5.5 mil (125-138 μ)	5.0 - 5.5 mil (125-138 μ)	5.0 - 5.5 mil (125-138 μ)
Tack Level		Low	Medium	High
Adhesion to Steel*		7 - 9 N/100 mm (6 - 8 oz)	13 - 15 N/100 mm (12 - 14 oz)	18 - 20 N/100 mm (16 - 18 oz)
Die-Cut Graphics Size		Large	Mid-Sized	Mid-Sized
Tensile		297 N/100 mm (17 lb/in)	297 N/100 mm (17 lb/in)	297 N/100 mm (17 lb/in)
Elongation		3-4%	3-4%	3-4%
Tear Resistance		50	50	50
Shelf Life		1 Year	1 Year	1 Year

\* TEST METHOD: PSTC-101



**WARRANTY** Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.