

## ▶ DPF 510 ULTRA TACK

### Digital Print Pressure-Sensitive Ultra Tack Vinyl Film

DPF 510 Ultra Tack is a 100 microns monomeric film with a clear or tinted, solvent-based, pressure-sensitive, ultra tack adhesive. The two-sided polycoated liner provides excellent lay-flat properties. The high tack adhesive provides superior adhesion for multi-purpose signage applications. DPF 510 Ultra Tack is available in a white gloss finish (DPF 510G-UT or DPF 510GT-UT) and white matte finish (DPF 510M-UT or DPF 510MT-UT). DPF 510 Ultra Tack is rated for outdoor durability up to 3 years (unprinted). Printed durability is dependent on the ink system used.

### APPLICATIONS & FEATURES

- Short-term promotional and display graphics
- Barricade graphics, tradeshow signage or construction graphics and interior floor graphics\*
- Ideal for interior and exterior applications on flat surfaces
- Excellent printability on Eco-Solvent, Solvent, and Latex print systems

\*When used with Series 3510 Matte.

### PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE
<b>SURFACE FINISH</b>	Gloss Meter 60° Reflection	70 to 90 Gloss Units (Gloss) Up to 30 Gloss Units (Matte)
<b>THICKNESS</b>	Micrometer, Federal Bench Type	100 microns
<b>TENSILE STRENGTH</b>	Tensile Tester with 51 mm jaw separation; crosshead speed of 12 in/min. 5.1 mm/s, web direction	≥ 1.8 kg/cm
<b>ELONGATION</b>	Instron Tensile Tester as above	≥ 150%
<b>SHELF LIFE (IN BOX)</b>	Ideal Storage Temperature 21°C and 50% relative humidity	1 year from factory shipment
<b>APPLICATION TEMPERATURE RANGE</b>	On clean, dry substrate	10°C to 32°C
<b>SERVICE TEMPERATURE RANGE</b>	On clean, dry substrate	-29°C to 65°C
<b>DIMENSIONAL STABILITY</b>	70°C, 48 hours	≥ 1.27mm
<b>PEEL ADHESION</b>	PSTC-1, 15 min, 21°C	≥21 N/25mm
<b>LINER RELEASE</b>	TLMI Release at 90°, 760 cm/min	7.0 g/cm

Standard Terms & Conditions Apply

#### USA

**a** 200 Boysenberry Lane, Placentia, CA 92870  
**p** 800 232 7161 / +1 714 985 6300  
**f** +1 714 985 6305

#### EUROPE

**a** Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands  
**p** +31 70 354 4311  
**f** +31 70 355 7721

#### CHINA

**a** No. 1989 Xinchang Road, Weifang, Shandong, 262400  
**p** +86 0536 6226568

## FLOOR APPLICATIONS

DPF 510 Ultra Tack is recommended for short-term interior floor applications such as smooth floors, sealed concrete, ceramic tile, waxed vinyl flooring, sealed wood, marble and terrazzo, when used with Series 3510 Matte, which is approved under the European Standard Certification EN 14041 for slip-resistance for Floor Graphic Materials. To determine the best product for application Arlon always recommends testing prior to using the above products on the actual surface as product performance can vary greatly depending on the surface type, level of foot traffic, elemental exposure, and floor condition. Due to these variables, Arlon only warrants the material(s) for standard manufacturers defect and is unable to offer a warranty for the performance or clean removability of these products for floor graphic applications.

Please refer to Arlon's Installation Guide for detailed techniques and best practices.




## TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:




All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

April 2020



### USA

 200 Boysenberry Lane, Placentia, CA 92870  
 800 232 7161 / +1 714 985 6300  
 +1 714 985 6305

### EUROPE

 Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands  
 +31 70 354 4311  
 +31 70 355 7721

### CHINA

 No. 1989 Xinchang Road, Weifang, Shandong, 262400  
 +86 0536 6226568