



FIRST STRETCHABLE POLYURETHANE TEXTILPRESSUREFOLIE WITH SUBLIMATION LAMINATION!

With patented ONYX STiX² adhesive and an activated carbon barrier layer that keeps the material stretchy and supple despite the block-out function. A short time at a low temperature protects the textile surface. Adheres to almost all types of textiles. For highly sublimating textiles, we recommend our CAD-COLOR® Sublistop!



AVAILABLE IN

- 50 cm x 25 m roll

RECOMMENDED FABRICS * Test before application!

- 100% Cotton
- Polyester-Cotton blends
- Most nylon textiles*
- 100% Polyester*
- Lycra® - / Spandex blended

CUTTING NOTES

Always test the cutting settings before production. Remember that the settings depend on the age of the blade used. Cutting too deep will cause difficulties when weeding or pressing.

APPLICATION INSTRUCTIONS

Temperature: 150° C
Time: 10 sec. Repressing: 8 sec.
Pressure: Medium (#4-6 with Hotronix®)
Carrier: Warm peel

ACCESSORIES RECOMMENDED

- CAD-COLOR® MagicMask® High Tack
- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers
- Squeegee

CARE INSTRUCTIONS

Washable up to 40° C. Please do not use fabric softener or bleach. Suitable for tumble drying on a gentle setting. Wash and iron inside out.

STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.

