

PRODUCT: PR2303 Temporary Data Sheet



PRODUCT DESCRIPTION

Double-sided self-adhesive tape with cloth carrier, solvent natural rubber adhesive, removable.

LINER

80 gsm brown paper siliconised both sides

CARRIER

Cotton cloth

ADHESIVE

White, solvent natural rubber.

MAIN APPLICATIONS

Designed for applications in the flexographic printing sector. Also suitable for carpet, floor covering laying and bonding of materials with rough or porous surfaces. Suggested for lamination of textiles and leather.

FEATURES

High-tack and high coating weight adhesive which allows coupling on irregular surfaces. Clean removal from many surfaces.

TECHNICAL DATA (average values)

ELONGATION (AFERA 5004)	[%]	6
TENSILE STRENGTH (AFERA 5004)	[N/cm]	55
180° PEEL (AFERA 5001)	[N/25mm]	10
STATIC SHEAR (AFERA 5012)	[h]	<5
ROLLING BALL TACK (PSTC 6)	[cm]	<5
THICKNESS (AFERA 5006)	[μ]	350
THICKNESS LINER (AFERA 5006)	[μ]	70
PERFORMING TEMPERATURE	min -10°C	max +45 °C

DATE: 05/06/23

The product has a shelf life of 12 months when stored in original packaging at a temperature of 23 °C with a relative humidity of 50%. BO.MA products were developed based on high quality standards to give good results even in difficult conditions, and are regularly subjected to stringent controls. All information and recommendations contained in our publications are the result of theoretical and practical experiences and provide the best of current knowledge. However, they do not involve any form of guarantee, either direct or implied, regarding the suitability of the product to a particular application, nor can they be considered as a basis for technical specifications. Therefore, determining whether the product BO.MA is appropriate for a specific application or technology is of the user's responsibility. It is therefore advisable to run tests in order to verify the suitability of the tape BO.MA chosen for your application and for the specific performance requirements. BO.MA engineers are always available to help.